Declaration of Performance



Glasroc® X Sheathing Board

((

| 1 | Unique identification code of the product type: | Glasroc X Sheathing Board |
|---|--|---|
| 2 | Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4): | Glasroc X Sheathing Board: 12.5mm |
| 3 | Intended use/s: | Gypsum board with mat reinforcement for exterior wall linings |
| 4 | Manufacturer: | Saint-Gobain Construction Products CZ a.s. Divize Rigips Smrčkova 2485/4 180 00 Praha 8-Libeň Czech Republic |
| 5 | Authorised representative: | N/A |
| 6 | System/s of AVCP: | System 3 |
| 7 | Harmonised standard: | EN 15283-1:2008 + A1:2009 |
| | Notified body/ies: | Centrum stavebniho inženýrstvi.a.s., Praha 10 |
| | | Notified body No. 1390, performed the testing of the product type for reaction to fire and issued the classification protocol No. PK-16-032 |
| 8 | European Assessment Document: | N/A |
| | European Technical Assessment: | N/A |
| | Technical Assessment Body: | N/A |
| | Notified body/ies: | N/A |
| 9 | Declared performance/s: | The characteristics in the table below apply to all products mentioned in 2 above. |

| Essential characteristics | Performance | Harmonised technical specification |
|---|-------------------------------|------------------------------------|
| Shear strength (↓↑) | NPD | EN 15283-1:2008 + A1:2009 |
| Reaction to Fire (R2F) | A1 | EN 15283-1:2008 + A1:2009 |
| Water vapour permeability (μ) | 18.2 | EN 15283-1:2008 + A1:2009 |
| Thermal conductivity (λ) | 0.1865W/mK | EN 15283-1:2008 + A1:2009 |
| Water absorption | H1 | EN 15283-1:2008 + A1:2009 |
| Flexural strength (F) | >540 | EN 15283-1:2008 + A1:2009 |
| Dangerous Substances (DS) | NPD | EN 15283-1:2008 + A1:2009 |
| Direct airborne sound insulation ¹ (R) | See manufacturer's literature | EN 15283-1:2008 + A1:2009 |

¹ These characteristics are system dependent and will be provided in manufacturer's literature based upon intended use. Performance declared is for the system of which the product is a part.

Declaration of Performance



Glasroc® X Sheathing Board

 ϵ

10 Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulations (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Om of Die

East Leake 10/2/2022

Dean O'Sullivan, Managing Director, British Gypsum

Place and date of issue