# SШISSPEARL

### Declaration of Performance No. 029/DoP

In accordance with Regulation (EU) No 305/2011 of the European Parliament and of the Council laying down harmonised conditions for the marketing of construction products (CPR EU 305/2011)

1. Unique identification code of the product-type:

### Fibre-cement flat sheets

Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Swisspearl Patina Original NXT (Swisspearl Patina Original, Cembrit Cembonit, Cembrit Classic, Cementmood, Cembrit Plan, Planatural)

2. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Flat sheets Internal wall finishes External wall and ceiling finishes

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Swisspearl Group AG Eternitstrasse 3 CH-8865 Niederurnen, Switzerland Email: <u>info@swisspearl.com</u>

4. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

#### Not applicable

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

AVCP System 3 / System 4

### SШISSPEARL

6a. Name and identification number of the notified body (in case of the declaration of performance concerning a construction product covered by a harmonised standard):

For products manufactured according to system 3

CSI SpA Viale Lombardia, 20 20021 Bollate MI – Italy Notified body No. 0497

Notified Body performed initial type- and acceptance testing according EN12467. Test Report CSI-CERT-no. DE/4529/12, Issued, 29. March 2012.

Exova Warringtonfire Helmsfield Road, Warrington, WA1 2DS, United Kingdom Notified body No. 0833

Notified Body performed reaction to fire testing and classification according EN 13501-1. Test report no. WFR 348118 dated 4. March 2015.

#### For products manufactured according to system 4

For CI:

Manufacturer performed the Initial Type Test according to EN 12467. Test report no.: 34-4-ITT-20170317, dated 15th March 2017 and 34-41-ITT-20211229, dated 29th December 2021.

For CII: Manufacturer performed the Initial Type Test according to EN 12467. Test report no.: 34-48, dated August 29<sup>th</sup> 2023. Test report no.: 34-52-1, dated November 16<sup>th</sup> 2023 and Test report no.: 34-52-2, dated November 16<sup>th</sup> 2023.

For CI: ASOCIACION PARA EL FOMENTO DE LA INVESTIGATIÓN Y LA TECNOLOGIA DE LA SEGURIDAD CONTRA INCENDIOS (AFITI-LICOF) Notified body No. 1168 Camino del Estrechillo, 8 E-28500 Arganda del Rey Madrid, Spain.

Notified Body performed reaction to fire and classification according EN 13501-1. Classification report no. 3233T17-3, dated 22nd February 2021 (Patina w/white core) and classification report no. 3234T17-3, dated 22nd February 2021 (Patina w/Grey core)

For Cll: ITB Fire Research Department Notified body No. 1488 1 Filtrowa Str. 00-611 Warszawa Poland

Notified Body performed reaction to fire and classification according EN 13501-1. Classification report no.: 02496.2/23/Z00NZP-ENG

## SШISSPEARL

6b. Name and identification number of the Technical Assessment Body (in case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued):

### Not applicable

7. Declared performance:

Essential characteristics	Performance	Harmonised technical specification
Type of sheets	NT	
Intended use category	A	
Class of strength	4	
Mechanical resistance	Min. 18 MPa	
Reaction to fire	Class A2-s1, d0	EN 12467:2012+A2:2018
Water impermeability	No water drops	Fibre-cement flat sheets
Dimensional variations	Level I	Product specification
Release of dangerous substance	No performance determined	and test methods
Durability against warm water	R <sub>L</sub> ≥ 0,75	
Durability against soak/dry	R <sub>L</sub> ≥ 0,75	
Durability against freeze-thaw	R <sub>L</sub> ≥ 0,75	
Durability against heat-rain	Pass	

8. Appropriate Technical Documentation and/or Specific Technical Documentation:

### EN 12467:2012+A2:2018 Fibre-cement flat sheets Product specification and test methods

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

Joachim Ebenhoch Global Head of Innovation Swisspearl Group AG

Niederurnen, 01.09.2024