



Declaration of Performance

1000.UKDoP.KRocFS.005

Designated technical specification:

Unique identification code of the product-type:

Intended use/es:
Manufacturer:
System/s of AVCP:

K-Roc Framing Slab

Thermal insulation for buildings

Kingspan Insulation Ltd, Herefordshire HR6 9LA, UK System 1 (for Reaction to Fire), System 3 (for other

properties).

BS EN 13162:2012+A1:2015

UK Assessment/Notified body/ies: BBA: 0836

| K Assessment/Notified body/ies: BBA: 0836 | | | | |
|--|--|-------------|--|--|
| Essential characteristics | | Performance | | |
| Thermal resistance | T | Refer to ML | | |
| | Thermal resistance R _D ((m².K)/W) | | | |
| | Thermal conductivity λ_D (W/(m.K)) | 0.036 | | |
| | Thickness tolerance | Т2 | | |
| Reaction to fire | Euroclass | A1 | | |
| Durability of reaction to fire against heat, weathering, ageing / degradation | Durability of RtF fire properties | Al | | |
| Durability of Thermal Resistance Against Heat, Weathering, Ageing/Degradation | Durability of Thermal properties | 0.036 | | |
| Dimensional stability under specified temperature and humidity condition | Dimensional stability | DS(70,) | | |
| Durability of compressive strength against ageing/degradation | Compressive creep | NPD | | |
| Compressive strength and stress | Compressive stress | NPD | | |
| | Compressive strength | NPD | | |
| | Point load PL(5) | NPD | | |
| Direct airborne sound insulation index | Air Flow Resistivity AFR | NPD | | |
| Durability of compressive strength against ageing / degradation | Compressive creep | NPD | | |
| Water permeability | Short term water absorption | ≤ 1 kg/m² | | |
| | Long term water absorption | ≤ 3 kg/m² | | |
| Water vapour permeability | Water vapour diffusion resistance factor | Mu 1 | | |
| | Water Vapour Resistance Z | NPD | | |





Declaration of Performance

| Impact noise transmission index (for floors) | Dynamic Stiffness SD | NPD | |
|---|---|-----|--|
| Tensile flexural strength | Tensile Strength Perpendicular to Faces TR, amt | NPD | |
| Acoustic absorption index | Sound absorption | NPD | |
| Release of dangerous substances to the indoor environment | Release of dangerous substances | NPD | |
| Continuous glowing combustion | Glowing combustion | NPD | |
| NPD: No Performance Determined | | | |

ML – Manufactures Literature

EU Regulation 305/2011, as retained in UK law, and as amended by SI no. 465/2019 (the Construction Products (Amendment etc.) (EU Exit) Regulations 2019) and SI no. 1359/2020 (the Construction Products (Amendment etc.) (EU Exit) Regulations 2020.)

For System 1 AVCP Notified certification body No 0836 Performed, carried out the determination of the product type, the inspection of the manufacturing plant and factory production control and continuous surveillance, assessment and evaluation of the factory production control, and issued the certificate of constancy of performance for reaction to fire, cert No UK 0836-CPR-22/P6091

Notified testing lab 0836 Performed the test reports for the other relevant declared characteristics (AVCP 3 properties).

Signed for and on behalf of the manufacturer by:

Siobhan O'Dwyer Managing Director

Pembridge, England, UK Date signed: 05/07/2024 Issue Number: 005



For the most up-to-date version of the Declaration of Performance please scan or <u>click here</u>.

To access pre-existing product information or information relating to previously sold/discontinued products please email literature@kingspaninsulation.co.uk.